

Product Data Sheet

SMOKE-FREE SF-10™

General Information

- Designed to seal gaps between cylinder walls & piston rings to reduce oil consumption & excessive exhaust smoke
- Contains MPC's MT-10 Metal Treatment™ to help reduce friction-related heat & wear

Key Features & Benefits

- Eliminates excessive exhaust smoke
- Reduces oil consumption
- Reduces noise from valves & lifters
- Improves engine performance & efficiency
- Reduces high friction-related heat & wear in the engine

Typical Applications

- All types of vehicles: Cars, light & heavy-duty trucks, commercial vehicles, fleets, etc.
- Recommended for both gasoline & diesel engines

Directions for Use

Add one 12-oz. bottle of Smoke-Free SF-10™ to the oil in the crankcase at or between oil changes. When adding between oil changes, do not overfill. Add SF-10 to the engine when it is idling at operating temperature.

Availability

- 12-oz. bottle

Typical Properties

Boiling point > 380°F
Flash point > 300°F PMCC
Specific gravity @ 60°F 0.91
Vapor density (air = 1) N/A
Vapor pressure (mm Hg) < 0.01 @ 25°C
Evaporation rate (butyl acetate = 1) < 0.01
Viscosity 5,500 SUS
Odor Mild petroleum
Color Amber
Appearance High viscosity liquid
Solubility in Water Insoluble

Material Safety Data

- **Ingestion:** Do not induce vomiting. Call a physician immediately.
- **Eye Contact:** Flush with water for 15 minutes. Call a physician if irritation persists.
- **Skin Contact:** Wash thoroughly with soap & water. Call a physician if irritation occurs.
- **Storage:** Do not store in temperatures above 130°F.
- For additional information, please refer to Material Safety Data Sheet (MSDS).

Freight Classification

- **Classification:** Lubricating oil
- **Hazard Class:** Nonhazardous
- **Packing Group:** N/A



"The Strength in Lubrication"®

752 Kilgore Road
Jackson Center, PA 16133
Phone: 800-227-7049
814-786-0166
Fax: 814-786-7321
Website: www.mpclubricants.com

Copyright 1998-2005 Musde Products Corp.
Rev. 8/2005